

Paging System ARAS 300

Product Description



The paging system ARAS 300 consists of:

- 1 Piece Control console BP 301 with one button and LED control light, 3 m connection cable and modular (western) plug and socket (AP), metal casing, silver grey, W 86 x L 65 x H 16 mm
- 1 Piece Mains adaptor NT 500 with 230 V plug and modular (western) plug and socket (AP)
- 1 Piece Display board AT 302 with 2 controllable display lines,
 - 1. line with the caption "please wait" and a red light in front of it
 - 2. line with the caption "please enter" and a green flashing light in front of it with adjustable 3-tone chimeincluding control unit for up to 5 control consoles, with 0.3 m connection cable and modular (western) plug and socket (AP) metal casing, silver grey, W 350 x H 150 x D 32 mm, for mounting on wall

Up to 5 control consoles can be connected to one display board.

Function:

Using the button at the control console the red light at the display board gets off and the green light in front of the line "please enter" flashes. Thereupon the 3-tone chime built into the display board sounds and indicates to the visitor that it is his turn. The LED control light on the control console flashes during the call.

By repeated operation of the button or after 20 sec-

onds the system automatic switches the red light in front of the line "please wait" on.

If the button is pressed down more than 2 seconds, it does not switch automatic, but if the button is pressed again.

The automatic switching can be fixed at 10, 20, 30, 40, 50 or 60 seconds or can be turned off.

Alterations to incorporate recent technical developments reserved 07/03

ARAS Paging Systems

HAHN GmbH Ingenieurbüro Bismarckstr. 16 D-12169 Berlin ☎ (+4930) 794 894-0 Fax: (+4930) 794 894-44
www.aras-aufrufanlagen.de email: hahn-aras@t-online.de